


■ PD14AM Series

Features 特点

- The optimal design realizes high quality sound and low distortion.
高音质、低失真最佳设计
- Compact size using flat wire.
扁平线小尺寸封装
- Small compact, and DIP type.
小体积，直插类型
- Low radiation noise by magnetically shielded construction
闭合磁路封装，低辐射
- High current, Low resistance.
大电流，低电阻
- Operating temperature : -40°C~+125°C.
工作温度：-40°C~+125°C



Applications 应用

- Suitable as choke for digital amp. Car audio, LCD and PDP TV, 5.1ch Home theater, etc.
适用于数字功放扼流。如汽车音响，LCD 电视和 PDP 电视，5.1 声道家庭影院等

Electrical characteristics 电气特性



Part number 料号	Inductance ① 电感量 $\mu\text{H} \pm 10\%$	DCR ② 直流电阻 mΩ		SRF ③ 自谐频率 MHz	Isat ④ 直流饱和电流 A typical			Irms ⑤ 温升电流 A typical	
		typ	max.		typical	10% drop	20% drop	30% drop	20°C rise
PD14AM-103KL	10	7.5	8.3	18	14.5	15.5	15.9	5.7	7.4
PD14AM-153KL	15	6.9	7.8	12	12	12.8	13.1	5.8	7.5
PD14AM-223KL	22	8.3	9.5	8	7.2	7.85	8.1	5.6	7.2
PD14AM-273KL	27	13.2	14.5	6	7.1	7.7	7.9	4.7	6.0
PD14AM-333KL	33	14.1	15.8	5	6.6	7.1	7.3	4.5	5.7

Remark

- ① Inductance is measured with a LCR meter Agilent 4284A or equivalent.
Test frequency at 100kHz
- ② DC resistance is measured with keithley 580 Milliohm Meter , or equivalent.
Reference ambient temperature 25°C
- ③ SRF measured using an Agilent 4395A network analyzer and an Agilent 16193A test fixture.
- ④ DC current at 25°C that causes the specified Inductance drop from its value without current.
- ⑤ Current that causes the specified temperature rise from 25°C ambient. This information is for reference only and does not represent absolute maximum ratings.
- ⑥ Electrical specifications at 25°C


备注

- ① 电感量测试采用 Agilent 4284A 数字电桥或同等仪器；
测试频率 100KHz
- ② 直流电阻测试采用 keithley 580 毫欧表或同等仪器；
环境温度 25° C
- ③ SRF 使用 Agilent 4395A 网络分析仪和 Agilent 16193A 测试夹具测量。
- ④ 直流电流在 25° C，加载导致指定电感从没有电流的值下降。
- ⑤ 导致指定温度从 25° C 环境温度上升的电流。此信息仅供参考，不代表绝对最大额定值。
- ⑥ 25° C 时的电气规格

Dimensions 结构尺寸**Electrical Characteristic Curve 电气特性曲线**

■ Packaging Specification - tray: [mm]

包装规格 - 托盘包装: [mm]



Weight 重量: 8.75~9.1g/PCS
Packaging 包装数量: 54 PCS/盘